

# PRODUCT SPECIFICATION

REFERENCE NO: QAP / 03 / D4



**HAYCARB**  
Activated carbon solutions

## RWAP 1472

SPECIFICATION	VALUE	TEST METHOD
Iodine Number (mg/g)	Min: 1000	ASTM
Apparent Density (g/cc) - Dry	Min: 0.51	ASTM
Moisture (% by wt)	Max: 5	ASTM
Total Ash (% by wt)	Max: 3	ASTM
Hardness Number	Min: 98	ASTM
Extractable pH	9-11	ASTM
<b><u>Particle size 8X30 ASTM mesh</u></b>		
> 8mesh ( 2.360 mm ) (% by wt)	Max: 5	ASTM
8X30 ( 2.360 mm x 0.600 mm ) (% by wt)	Min: 90	ASTM
< 30 mesh ( 0.600 mm ) (% by wt)	Max: 5	ASTM

**\*NSF61 CERTIFIED PRODUCT.**

Spec No : 8722

Date : 21-10-2021



Haycarb Activated Carbon grades that are Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only, are listed on: [www.nsf.org/certified/DWTU](http://www.nsf.org/certified/DWTU)

Component



ISO 9001:2008 Certified



ISO 14001:2004 Certified



[www.haycarb.com](http://www.haycarb.com)